



hardy spicer

• HOSE • FITTINGS • DRIVESHAFTS



Crimp Data Catalogue

Solutions for Industrial & Hydraulic Applications

hardyspicer.com.au

Disclaimer

The information and dimensions listed in this catalogue is correct to the best of our knowledge and belief, having been compiled from reliable and official sources of information. However Hardy Spicer (HS Company Pty Ltd) accepts no responsibility for possible errors, omissions or unsuitable parts being listed or fitted to any vehicle. Due to our continuous product and range development we reserve the right to alter the specification without prior notice. The digital setting and die sets relate to the Gates GC32-XD crimp machine using Gates matched hose and fittings. Crimp data may sometimes change. Printed crimp specifications are uncontrolled, and should be re-printed every 6 months or any time a new eCrimp revision is released. All settings are APPROXIMATE. Always check the final crimp OD to ensure the crimp has been properly formed. Refer to electronic crimp data at ecrimp.gates.com for the current crimp settings.

We welcome any feedback re suspected errors or omissions to the information enclosed. We can be contacted via email hspicer@hardyspicer.com.au Or via Ph 03 9794 1900 or Fax 03 9706 9928 Alternatively via mail at PO Box 4262, Dandenong South, Vic. 3164.

GC32-XD CRIMPER



- Part No:** GC32-XD
- Description:** Powerful hydraulic crimper
- Features:** The new GC32-XD crimper crimps fittings up to 2 1/2". The open crimper head accommodates most hose construction or fitting configuration. The unique cloverleaf* design produces a smoother, better and more consistent crimp without any tapers in the crimp OD. A quick change tool enables fast loading of the colour coded, numbered dies.

Power Source: Single phase 20 amp plug

www.hardyspicer.com.au

Document No:	HSCRIMPCAT
Issue:	15.1
Issue Date:	28/01/21

This catalogue is the copyright of Hardy Spicer

Wire Braid Hose

Hose Part Number	Size (in.)	Fitting Type	Ferrule Description	Skive Lgth +/- 0.76(mm)	Die Set	Digital Setting	Crimp OD +/- 0.25(mm)
G1-04	1/4	4G-	MegaCrimp	-----	32-21	0.85	17.90
G1-06	3/8	6G-	MegaCrimp	-----	32-22	1.61	21.60
G1-08	1/2	8G-	MegaCrimp	-----	32-33	1.60	25.15
G1-10	5/8	10G-	MegaCrimp	-----	32-34	0.47	28.60
G1-12	3/4	12G-	MegaCrimp	-----	32-35	1.39	34.05
G1-16	1	16G-	MegaCrimp	-----	32-37	1.77	44.45
G1-20	1 1/4	20G-	MegaCrimp	-----	32-39	0.46	52.05
G1-24	1 1/2	24GSP-	GSP-24-1F-2	-----	32-310L	2.52	58.40
G1-32	2	32GSP-	GSP-32-1F-2	-----	32-312	2.19	71.10

CR1-04	1/4	4G-	MegaCrimp	-----	32-21	0.83	17.90
CR1-06	3/8	6G-	MegaCrimp	-----	32-22	2.00	21.60
CR1-08	1/2	8G-	MegaCrimp	-----	32-33	0.61	25.15
CR1-10	5/8	10G-	MegaCrimp	-----	32-34	0.37	28.60
CR1-12	3/4	12G-	MegaCrimp	-----	32-35	1.48	34.05
CR1-16	1	16G-	MegaCrimp	-----	32-37	1.53	44.45

G2-04	1/4	4G-	MegaCrimp	-----	32-21	1.65	18.80
G2-06	3/8	6G-	MegaCrimp	-----	32-22	2.62	22.60
G2-08	1/2	8G-	MegaCrimp	-----	32-33	2.22	26.65
G2-10	5/8	10G-	MegaCrimp	-----	32-34	1.26	29.70
G2-12	3/4	12G-	MegaCrimp	-----	32-35	2.40	35.45
G2-16	1	16G-	MegaCrimp	-----	32-37	2.46	45.20
G2-20	1 1/4	20G-	MegaCrimp	-----	32-39	2.08	54.00
G2-24	1 1/2	24GSP-	GSP-24-1F-2	-----	32-310L	4.00	60.05
G2-32	2	32GSP-	GSP-32-1F-2	-----	32-312	3.55	72.90

CR2-04	1/4	4G-	MegaCrimp	-----	32-21	1.65	18.80
CR2-06	3/8	6G-	MegaCrimp	-----	32-22	2.60	22.60
CR2-08	1/2	8G-	MegaCrimp	-----	32-33	2.22	26.65
CR2-10	5/8	10G-	MegaCrimp	-----	32-34	1.26	29.70
CR2-12	3/4	12G-	MegaCrimp	-----	32-35	2.75	35.45
CR2-16	1	16G-	MegaCrimp	-----	32-37	1.87	45.20

www.hardyspicer.com.au

Document No:	HSCRIMPCAT
Issue:	15.1
Issue Date:	28/01/21

This catalogue is the copyright of Hardy Spicer

Note: Die Set and Digital Setting information are to suit the Gates GC32-XD crimper only. Hose with XTF & MTF variations use the same crimp dimensions as the standard hose.

Hose Part Number	Size (in.)	Fitting Type	Ferrule Description	Skive Lgth +/- 0.76(mm)	Die Set	Digital Setting	Crimp OD +/- 0.25(mm)
G1H-04	1/4	4G-	MegaCrimp	-----	32-21	1.19	18.30
G1H-06	3/8	6G-	MegaCrimp	-----	32-22	1.61	21.45
G1H-08	1/2	8G-	MegaCrimp	-----	32-33	1.53	25.90
G1H-10	5/8	10G-	MegaCrimp	-----	32-34	0.47	28.85
G1H-12	3/4	12G-	MegaCrimp	-----	32-35	1.39	34.30
G1H-16	1	16G-	MegaCrimp	-----	32-37	1.77	44.70
G1H-20	1 1/4	20G-	MegaCrimp	-----	32-39	0.46	52.05
G1H-24	1 1/2	24GSP-	GSP-24-1F-2	-----	32-310L	2.52	58.40
G1H-32	2	32GSP-	GSP-32-1F-2	-----	32-312	2.19	71.10

G2XH-04	1/4	4G-	MegaCrimp	-----	32-21	1.65	18.80
G2XH-06	3/8	6G-	MegaCrimp	-----	32-22	2.62	22.60
G2XH-08	1/2	8G-	MegaCrimp	-----	32-33	2.22	26.65
G2XH-10	5/8	10G-	MegaCrimp	-----	32-34	1.26	29.70
G2XH-12	3/4	12G-	MegaCrimp	-----	32-35	2.40	35.45
G2XH-16	1	16G-	MegaCrimp	-----	32-37	1.77	44.70
G2XH-20	1 1/4	20G-	MegaCrimp	-----	32-39	2.08	54.00
G2XH-24	1 1/2	24GSP-	GSP-24-1F-2	-----	32-310L	4.00	60.05
G2XH-32	2	32GSP-	GSP-32-1F-2	-----	32-312	3.55	72.90

G2H-20	1 1/4	20G-	MegaCrimp	-----	32-39	2.08	54.00
G2H-24	1 1/2	24GSP-	GSP-24-1F-2	-----	32-310L	4.00	60.05
G2H-32	2	32GSP-	GSP-32-1F-2	-----	32-312	3.65	72.90

GMV-12	3/4	12G-	MegaCrimp	-----	32-35	3.19	36.30
GMV-16	1	16G-	MegaCrimp	-----	32-37	2.69	45.70
GMV-20	1 1/4	20G-	MegaCrimp	-----	32-39	1.76	53.60
GMV-24	1 1/2	24GSP-	GSP-24-1F-2	-----	32-310L	1.45	56.90
GMV-32	2	32GSP-	GSP-32-1F-2	-----	32-312	2.15	70.85
GMV-40	2 1/2	40GL-	1-pc GL	-----	32-86	1.10	72.15
GMV-48	3	48GL-	1-pc GL	Die Set Required			
GMV-56	3 1/2	56GL-	1-pc GL	Die Set Required			
GMV-64	4	64GL-	1-pc GL	Die Set Required			

MULTIMASTER-12	3/4	12G-	MegaCrimp	-----	32-35	4.12	37.15
MULTIMASTER-16	1	16G-	MegaCrimp	-----	32-37	1.06	44.00
MULTIMASTER-20	1 1/4	20G-	MegaCrimp	-----	32-38	3.25	51.00
MULTIMASTER-24	1 1/2	24GSP-	GSP-24-1F-2	-----	32-310L	1.30	57.05
MULTIMASTER-32	2	32GSP-	GSP-32-1F-2	-----	32-312	1.80	70.65
MULTIMASTER-40	2 1/2	40GL-	1-pc GL	-----	32-86	1.30	72.40

Note: Die Set and Digital Setting information are to suit the Gates GC32-XD crimper only.
 Hose with XTF & MTF variations use the same crimp dimensions as the standard hose.

www.hardyspicer.com.au

Document No:	HSCRIMPCAT
Issue:	15.1
Issue Date:	28/01/21

This catalogue is the copyright of Hardy Spicer

Crimp Dimensions

Hose Part Number	Size (in.)	Fitting Type	Ferrule Description	Skive Lgth +/- 0.76(mm)	Die Set	Digital Setting	Crimp OD +/- 0.25(mm)
MXT-04	1/4	4G-	MegaCrimp	-----	32-21	1.08	18.15
MXT-05	5/16	5G-	MegaCrimp	-----	32-22	0.38	20.20
MXT-06	3/8	6G-	MegaCrimp	-----	32-22	1.51	21.20
MXT-08	1/2	8G-	MegaCrimp	-----	32-33	0.61	25.15
MXT-10	5/8	10G-	MegaCrimp	-----	32-34	0.37	28.85
MXT-12	3/4	12G-	MegaCrimp	-----	32-35	1.68	34.30
MXT-16	1	16G-	MegaCrimp	-----	32-37	0.30	42.80
MXG-06-XTP	3/8	6GS-	GS-06GS1F-2	-----	32-32	1.00	20.70
MXG-08-XTP	1/2	8GS-	GS-08GS1F-2	-----	32-22mm	1.30	23.20
MXG-10-XTP	5/8	10GS-	GS-10GS1F-2	-----	32-33	3.20	27.70
MXG-12-XTP	3/4	12GS-	GS-12GS1F-2	-----	32-35	0.52	33.25
MXG-16-XTP	1	16GS-	GS-16GS1F-4	-----	32-37	1.16	43.95
M2T-04	1/4	4G-	MegaCrimp	-----	32-21	1.08	18.15
M2T-06	3/8	6G-	MegaCrimp	-----	32-22	2.20	21.85
M2T-08	1/2	8G-	MegaCrimp	-----	32-33	1.88	26.30
M2T-10	5/8	10G-	MegaCrimp	-----	32-34	0.25	28.60
M2T-12	3/4	12G-	MegaCrimp	-----	32-35	1.84	34.80
M2T-16	1	16G-	MegaCrimp	-----	32-37	0.63	43.45
CM2T-06-XTF	3/8	6G-	MegaCrimp	-----	32-22	2.20	21.85
CM2T-08	1/2	8G-	MegaCrimp	-----	32-33	1.88	26.30
M3K-04	1/4	4G-	MegaCrimp	-----	32-21	0.73	17.80
M3K-06	3/8	6G-	MegaCrimp	-----	32-22	0.83	20.55
M3K-08	1/2	8G-	MegaCrimp	-----	32-33	1.07	25.40
M3K-10	5/8	10G-	MegaCrimp	-----	32-34	1.26	29.70
M3K-12	3/4	12G-	MegaCrimp	-----	32-35	2.40	35.45
M3K-16	1	16G-	MegaCrimp	-----	32-37	2.69	45.70
M4K-04	1/4	4G-	MegaCrimp	-----	32-21	1.08	18.15
M4K-06	3/8	6G-	MegaCrimp	-----	32-22	2.17	21.85
M4K-08	1/2	8G-	MegaCrimp	-----	32-33	1.68	26.05
M4K-10	5/8	10G-	MegaCrimp	-----	32-34	0.83	29.35
M4K-12	3/4	12G-	MegaCrimp	-----	32-35	2.40	35.45
M4K-12	3/4	12GS-	GS-12GS1F-2	-----	32-35	0.27	33.00
M4K-16	1	16GS-	GS-16GS1F-2	-----	32-36	2.82	41.15
M4K-16	1	16GS-	GS-16GS1F-4	-----	32-37	0.64	43.70

www.hardyspicer.com.au

Document No:	HSCRIMPCAT
Issue:	15.1
Issue Date:	28/01/21

This catalogue is the copyright of Hardy Spicer

Note: Die Set and Digital Setting information are to suit the Gates GC32-XD crimper only. Hose with XTF & MTF variations use the same crimp dimensions as the standard hose.

Hose Part Number	Size (in.)	Fitting Type	Ferrule Description	Skive Lgth +/- 0.76(mm)	Die Set	Digital Setting	Crimp OD +/- 0.25(mm)
M5K-04	1/4	4G-	MegaCrimp	-----	32-21	1.08	18.15
M5K-06	3/8	6G-	MegaCrimp	-----	32-22	1.95	21.85
M5K-08	1/2	8G-	MegaCrimp	-----	32-33	1.99	26.40
M6K-04	1/4	4G-	MegaCrimp	-----	32-21	1.65	18.80
J2AT-04	1/4	4G-	MegaCrimp	-----	32-21	1.65	18.80
J2AT-06	3/8	6G-	MegaCrimp	-----	32-22	2.73	22.75
MT250-04	1/4	4G-	MegaCrimp	-----	32-21	0.73	17.25
MT250-06	3/8	6G-	MegaCrimp	-----	32-22	1.72	21.60
MT250-08	1/2	8G-	MegaCrimp	-----	32-33	0.61	24.90
MT250-10	5/8	10G-	MegaCrimp	-----	32-33	2.22	26.65
MT250-12	3/4	12G-	MegaCrimp	-----	32-35	1.16	34.05
MT250-16	1	16G-	MegaCrimp	-----	32-37	1.08	43.95
MT250-20	1 1/4	20G-	MegaCrimp	-----	32-38	2.58	50.30
MT500-24	1 1/2	24GSP-	GSP-24-1F-2	-----	32-310L	1.76	57.40
MT500-32	2	32GSP-	GSP-32-1F-2	-----	32-312	1.50	70.60
MT500-40	2 1/2	40GL-	1-pc GL	-----	32-86	0.55	71.10
MT500-48	3	48GL-	1-pc GL	Die Set Required			86.60
MT1000-04	1/4	4G-	MegaCrimp	-----	32-21	0.73	17.80
MT1000-06	3/8	6G-	MegaCrimp	-----	32-22	0.83	20.60
MT1000-08	1/2	8G-	MegaCrimp	-----	32-33	0.61	24.90
MT1000-10	5/8	10G-	MegaCrimp	-----	32-34	1.03	29.50
MT1000-12	3/4	12G-	MegaCrimp	-----	32-35	2.00	33.70
MT1000-16	1	16G-	MegaCrimp	-----	32-37	0.39	43.20
MT1000-20	1 1/4	20G-	MegaCrimp	-----	32-38	3.44	51.30
ACP-20	1 1/4	20G-	MegaCrimp	-----	32-39	2.08	54.00
ACP-24	1 1/2	24GSP-	GSP-24-1F-2	-----	32-310L	3.96	59.95
ACP-32	2	32GSP-	GSP-32-1F-2	-----	32-312	3.65	72.90

Note: Die Set and Digital Setting information are to suit the Gates GC32-XD crimper only.
 Hose with XTF & MTF variations use the same crimp dimensions as the standard hose.

Document No:	HSCRIMPCAT
Issue:	15.1
Issue Date:	28/01/21

Crimp Dimensions

Hose Part Number	Size (in.)	Fitting Type	Ferrule Description	Skive Lgth +/- 0.76(mm)	Die Set	Digital Setting	Crimp OD +/- 0.25(mm)
C5C-08	13/32	6G-	MegaCrimp	-----	32-32	2.60	22.50
C5M-05	1/4	4G-	MegaCrimp	-----	32-21	2.05	18.90
C5M-06	5/16	5G-	MegaCrimp	-----	32-22	1.90	21.60
C5M-08	13/32	6G-	MegaCrimp	-----	32-22	4.30	22.35
C5M-10	1/2	8GS-	GS-08GS1F-4	-----	32-33	1.40	27.70
C5M-12	5/8	10GS-	GS-10GS1F-4	-----	32-34	3.80	32.50
C5M-16	7/8	12G-	MegaCrimp	-----	32-35	4.10	35.80
C5CXH-05	1/4	4G-	MegaCrimp	-----	32-21	2.00	18.30
C5CXH-06	5/16	5G-	MegaCrimp	-----	32-22	0.70	20.45
C5CXH-08	13/32	6G-	MegaCrimp	-----	32-32	2.60	22.50
C5CXH-10	1/2	8GS-	GS-08GS1F-4	-----	32-33	3.02	27.70
C5CXH-12	5/8	10GS-	GS-10GS1F-4	-----	32-34	3.05	31.90
C5CXH-16	7/8	12G-	MegaCrimp	-----	32-35	2.40	35.30
C5CXH-20	1 1/8	16G-	MegaCrimp	-----	32-37	2.20	44.95
RFS-04	1/4	4G-	MegaCrimp	-----	32-21	0.85	17.90
RFS-06	3/8	6G-	MegaCrimp	-----	32-22	1.61	21.45
RFS-08	1/2	8G-	MegaCrimp	-----	32-33	1.30	25.65
RFS-12	3/4	12G-	MegaCrimp	-----	32-35	1.39	34.30
TH7-04	1/4	4G-	MegaCrimp	-----	32-21	1.08	18.15
TH7-06	3/8	6G-	MegaCrimp	-----	32-22	2.06	21.95
TH7-08	1/2	8G-	MegaCrimp	-----	32-33	1.65	26.05
TH7-12	3/4	12G-	MegaCrimp	-----	32-35	0.72	33.55
TH7-16	1	16G-	MegaCrimp	-----	32-37	0.16	42.95
TH8-04	1/4	4G-	MegaCrimp	-----	32-21	1.88	19.05
TH8-06	3/8	6G-	MegaCrimp	-----	32-22	2.40	22.35
TH8-08	1/2	8G-	MegaCrimp	-----	32-33	1.88	26.30
TH8-12	3/4	12G-	MegaCrimp	-----	32-35	1.39	34.30
TH8-16	1	16G-	MegaCrimp	-----	32-37	2.23	45.20

www.hardyspicer.com.au

Document No:	HSCRIMPCAT
Issue:	15.1
Issue Date:	28/01/21

This catalogue is the copyright of Hardy Spicer

Note: Die Set and Digital Setting information are to suit the Gates GC32-XD crimper only. Hose with XTF & MTF variations use the same crimp dimensions as the standard hose.

Hose Part Number	Size (in.)	Fitting Type	Ferrule Description	Skive Lgth +/- 0.76(mm)	Die Set	Digital Setting	Crimp OD +/- 0.25(mm)
GTH-03	3/16	3PC-	PC-03PC2FS	17.50	32-31	0.62	16.15
GTH-04	1/4	4G-	MegaCrimp	-----	32-21	1.88	19.05
GTH-05	5/16	5G-	MegaCrimp	-----	32-21	2.79	20.05
GTH-06	3/8	6G-	MegaCrimp	-----	32-22	1.72	21.60
GTH-08	1/2	8G-	MegaCrimp	-----	32-33	1.88	26.30
GTH-10	5/8	10G-	MegaCrimp	-----	32-34	0.90	29.30
GTH-12	3/4	12G-	MegaCrimp	-----	32-35	2.29	35.30
GTH-16	1	16G-	MegaCrimp	-----	32-37	0.63	43.45

RLA-04	1/4	4G-	MegaCrimp	-----	32-21	1.19	18.30
RLA-05	5/16	5G-	MegaCrimp	-----	32-21	2.34	19.55
RLA-06	3/8	6G-	MegaCrimp	-----	32-22	1.95	21.85
RLA-08	1/2	8G-	MegaCrimp	-----	32-33	2.92	27.45
RLA-10	5/8	10G-	MegaCrimp	-----	32-34	0.58	28.95
RLA-12	3/4	12G-	MegaCrimp	-----	32-35	3.19	36.30
RLA-16	1	16G-	MegaCrimp	-----	32-37	0.16	42.95

TERMINATOR-04	1/4	4G-	MegaCrimp	-----	32-21	1.65	18.80
TERMINATOR-06	3/8	6G-	MegaCrimp	-----	32-22	3.29	23.35
TERMINATOR-08	1/2	8G-	MegaCrimp	-----	32-33	2.22	26.65
TERMINATOR-12	3/4	12G-	MegaCrimp	-----	32-35	3.19	36.30
TERMINATOR-16	1	16G-	MegaCrimp	-----	32-37	2.35	45.35
TERMINATOR-20	1 1/4	20G-	MegaCrimp	-----	32-38	4.82	52.85
TERMINATOR-24	1 1/2	24GSP-	GSP-24-1F-2	-----	32-310L	1.15	58.15
TERMINATOR-32	2	32GSP-	GSP-32-1F-2	-----	32-313	2.54	74.30

Crimp Dimensions

www.hardyspicer.com.au

Document No:	HSCRIMPCAT
Issue:	15.1
Issue Date:	28/01/21

This catalogue is the copyright of Hardy Spicer

Spiral Hose

Hose Part Number	Size (in.)	Fitting Type	Ferrule Description	Skive Lgth +/- 0.76(mm)	Die Set	Digital Setting	Crimp OD +/- 0.25(mm)
EFG3K-24	1 1/2	24GSP-	GSP-24-1F-4	-----	32-311	2.38	62.00
EFG3K-32	2	32GSP-	GSP-32-1F-4	-----	32-313	2.92	74.55
EFG4K-06	3/8	6GS-	GS-06GS1F-4	-----	32-33	0.61	24.90
EFG4K-08	1/2	8GS-	GS-08GS1F-4	-----	32-33	2.92	27.45
EFG4K-10	5/8	10GS-	GS-10GS1F-4	-----	32-35	0.72	33.55
EFG4K-12	3/4	12GS-	GS-12GS1F-4	-----	32-35	4.31	37.60
EFG4K-16	1	16GS-	GS-16GS1F-4	-----	32-37	1.54	44.45
EFG4K-20	1 1/4	20GS-	GS-20GS1F-4	-----	32-39	0.46	52.05
EFG5K-06	3/8	6GS-	GS-06GS1F-4	-----	32-33	0.61	24.90
EFG5K-08	1/2	8GS-	GS-08GS1F-4	-----	32-33	2.92	27.45
EFG5K-10	5/8	10GS-	GS-10GS1F-4	-----	32-35	0.72	33.55
EFG5K-12	3/4	12GS-	GS-12GS1F-4	-----	32-35	4.31	37.60
EFG5K-16	1	16GS-	GS-16GS1F-4	-----	32-37	1.54	44.45
EFG5K-20	1 1/4	20GS-	GS-20GS1F-6	-----	32-310L	0.71	56.65
EFG5K-24	1 1/2	24GSH-	1 Piece	-----	32-311	3.88	63.75
EFG5K-24	1 1/2	24GSM-	1 Piece	-----	32-311	3.88	63.75
EFG5K-32	2	32GSH-	1 Piece	-----	32-314	0.45	77.85
EFG5K-32	2	32GSM-	1 Piece	-----	32-314	2.20	79.25
EFG6K-06	3/8	GS	GS-06GS1F-4	-----	32-33	0.61	24.90
EFG6K-08	1/2	GS	GS-08GS1F-4	-----	32-33	2.92	27.45
EFG6K-10	5/8	GS	GS-10GS1F-4	-----	32-35	0.72	33.55
EFG6K-12	3/4	GS	GS-12GS1F-4	-----	32-35	4.31	37.60
EFG6K-16	1	GS	GS-16GS1F-4	-----	32-37	1.54	44.45
EFG6K-20	1 1/4	GS	GS-20GS1F-6	-----	32-310L	0.71	56.65
EFG6K-24	1 1/2	24GSH-	1 Piece	-----	32-311	3.88	63.75
EFG6K-24	1 1/2	24GSM-	1 Piece	-----	32-311	3.88	63.75
EFG6K-32	2	24GSM-	1 Piece	-----	32-314	2.20	79.25

www.hardyspicer.com.au

Document No:	HSCRIMPCAT
Issue:	15.1
Issue Date:	28/01/21

This catalogue is the copyright of Hardy Spicer

Teflon Hose

Hose Part Number	Size (in.)	Fitting Type	Ferrule Description	Skive Lgth +/- 0.76(mm)	Die Set	Digital Setting	Crimp OD +/- 0.25(mm)
TF/1-03	3/16		MTF-03	-----			-
TF/1-04	1/4		MTF-04	-----			12.30
TF/1-05	5/16		MTF-05	-----			-
TF/1-06	3/8		MTF-06	-----			15.95
TF/1-08	1/2		MTF-08	-----			20.45
TF/1-10	5/8		MTF-10	-----			23.35
TF/1-12	3/4		MTF-12	-----			26.72
TF/1-16	1		MTF-16	-----			33.05

Refer to Hardy Spicer Product Bulletin # 41 for further information on teflon crimp specifications for MTF ferrules available from your local Branch.

Sabre Hose

Hose Part Number	Size (in.)	Fitting Type	Ferrule Description	Die Set	Digital Setting	Crimp OD +/- 0.1(mm)
SAB/R16-04	1/4	4G-	MegaCrimp	-	-	18.10
SAB/R16-06	3/8	6G-	MegaCrimp	-	-	21.90
SAB/R16-08	1/2	8G-	MegaCrimp	-	-	26.20
SAB/R16-12	3/4	12G-	MegaCrimp	-	-	34.70
SAB/R16-16	1	16G	MegaCrimp	-	-	43.50
PW/2-06-B-SEL	3/8	6G-	MegaCrimp	-	-	22.61

Note: Die Set and Digital Setting information are to suit the Gates GC32-XD crimper only. Hose with XTF & MTF variations use the same crimp dimensions as the standard hose.

www.hardyspicer.com.au

Document No:	HSCRIMPCAT
Issue:	15.1
Issue Date:	28/01/21

This catalogue is the copyright of Hardy Spicer

2 Piece Fittings

Hose Part Number	Size (in.)	Fitting Type	Ferrule Description	Skive Lgth +/- 0.76(mm)	Die Set	Digital Setting	Crimp OD +/- 0.25(mm)
G1-06	3/8	6GS-	GS-06GS1F-1	-----	32-18mm	2.20	20.05
G1-08	1/2	8GS-	GS-08GS1F-2	-----	32-22mm	0.85	22.85
G1-10	5/8	10GS-	GS-10GS1F-2	-----	32-33	2.30	26.80
G1-12	3/4	12GS-	GS-12GS1F-2	-----	32-34	3.70	32.25
G1-16	1	16GS-	GS-16GS1F-2	-----	32-36	2.62	40.65
G1-20	1 1/4	20GS-	GS-20GS1F-2	-----	32-38	2.17	49.80
G2-06	3/8	6GS-	GS-06GS1F-2	-----	32-32	1.50	21.35
G2-08	1/2	8GS-	GS-08GS1F-2	-----	32-22mm	1.90	23.90
G2-10	5/8	10GS-	GS-10GS1F-2	-----	32-33	3.00	27.45
G2-12	3/4	12GS-	GS-12GS1F-2	-----	32-35	0.27	33.00
G2-16	1	16GS-	GS-16GS1F-2	-----	32-36	3.03	41.40
G2-20	1 1/4	20GS-	GS-20GS1F-2	-----	32-38	4.00	51.80
G1H-06	3/8	6GS-	GS-06GS1F-1	-----	32-18mm	2.20	20.05
G1H-08	1/2	8GS-	GS-08GS1F-2	-----	32-22mm	0.85	22.85
G1H-10	5/8	10GS-	GS-10GS1F-2	-----	32-33	2.30	26.80
G1H-12	3/4	12GS-	GS-12GS1F-2	-----	32-34	3.70	32.25
G1H-16	1	16GS-	GS-16GS1F-2	-----	32-36	2.62	40.65
G1H-20	1 1/4	20GS-	GS-20GS1F-2	-----	32-38	2.17	49.80
G2XH-06	3/8	6GS-	GS-06GS1F-2	-----	32-32	1.50	21.35
G2XH-08	1/2	8GS-	GS-08GS1F-2	-----	32-22mm	1.90	23.90
G2XH-10	5/8	10GS-	GS-10GS1F-2	-----	32-33	3.00	27.45
G2XH-12	3/4	12GS-	GS-12GS1F-2	-----	32-35	0.27	33.00
G2XH-16	1	16GS-	GS-16GS1F-2	-----	32-36	3.03	41.40
G2XH-20	1 1/4	20GS-	GS-20GS1F-2	-----	32-38	4.00	51.80
G2H-20	1 1/4	20GS-	GS-20GS1F-2	-----	32-38	4.00	51.80
M2T-06	3/8	6GS-	GS-06GS1F-2	-----	32-32	1.00	20.70
M2T-08	1/2	8GS-	GS-08GS1F-2	-----	32-22mm	1.14	23.00
M2T-10	5/8	10GS-	GS-10GS1F-2	-----	32-33	2.80	27.20
M2T-12	3/4	12GS-	GS-12GS1F-2	-----	32-34	4.15	32.75
M2T-16	1	16GS-	GS-16GS1F-2	-----	32-36	0.35	38.35

www.hardyspicer.com.au

Document No:	HSCRIMPCAT
Issue:	15.1
Issue Date:	28/01/21

This catalogue is the copyright of Hardy Spicer

Note: Die Set and Digital Setting information are to suit the Gates GC32-XD crimper only. Hose with XTF & MTF variations use the same crimp dimensions as the standard hose.

Hose Part Number	Size (in.)	Fitting Type	Ferrule Description	Skive Lgth +/- 0.76(mm)	Die Set	Digital Setting	Crimp OD +/- 0.25(mm)
M2T-06-MTF	3/8	6GS-	GS-06GS1F-2	-----	32-32	1.00	20.70
M2T-08-MTF	1/2	8GS-	GS-08GS1F-2	-----	32-22mm	1.14	23.00
M2T-10-MTF	5/8	10GS-	GS-10GS1F-2	-----	32-33	2.80	27.20
M2T-12-MTF	3/4	12GS-	GS-12GS1F-2	-----	32-34	4.15	32.75
M2T-16-MTF	1	16GS-	GS-16GS1F-2	-----	32-36	0.35	38.35

CM2T-06	3/8	GS	GS-06GS1F-2	-----	32-32	1.00	20.70
CM2T-08	1/2	GS	GS-08GS1F-2	-----	32-22mm	1.14	23.00

CM2T-06-XTF	3/8	GS	GS-06GS1F-2	-----	32-32	1.00	20.70
CM2T-08-XTF	1/2	GS	GS-08GS1F-2	-----	32-22mm	1.14	23.00

MXT-06	3/8	6GS-	GS-06GS1F-2	-----	32-18mm	2.05	20.20
MXT-08	1/2	8GS-	GS-08GS1F-2	-----	32-22mm	1.10	23.00
MXT-10	5/8	10GS-	GS-10GS1F-2	-----	32-33	2.10	26.55
MXT-12	3/4	12GS-	GS-12GS1F-2	-----	32-34	3.05	31.50
MXT-16	1	16GS-	GS-16GS1F-2	-----	32-36	0.74	38.75

MXG-06-XTP	3/8	6GS-	GS-06GS1F-2	-----	32-32	1.00	20.70
MXG-08-XTP	1/2	8GS-	GS-08GS1F-2	-----	32-22mm	1.30	23.20
MXG-10-XTP	5/8	10GS-	GS-10GS1F-2	-----	32-33	3.20	27.70
MXG-12-XTP	3/4	12GS-	GS-12GS1F-2	-----	32-35	0.52	33.25
MXG-16-XTP	1	16GS-	GS-16GS1F-4	-----	32-37	1.16	43.95

M3K-06	3/8	6GS-	GS-06GS1F-1	-----	32-18mm	1.40	19.20
M3K-08	1/2	8GS-	GS-08GS1F-2	-----	32-22mm	0.90	22.75
M3K-10	5/8	10GS-	GS-10GS1F-2	-----	32-33	3.00	27.45
M3K-12	3/4	12GS-	GS-12GS1F-2	-----	32-35	0.27	33.00
M3K-16	1	16GS-	GS-16GS1F-2	-----	32-36	2.62	40.90


M4K-06	3/8	6GS-	GS-06GS1F-2	-----	32-32	1.00	20.70
M4K-08	1/2	8GS-	GS-08GS1F-2	-----	32-22mm	1.14	23.00
M4K-10	5/8	10GS-	GS-10GS1F-2	-----	32-33	3.00	27.45
M4K-12	3/4	12GS-	GS-12GS1F-2	-----	32-35	0.27	33.00
M4K-16	1	16GS-	GS-16GS1F-2	-----	32-36	2.82	41.15
M4K-16	1	16GS-	GS-16GS1F-4	-----	32-37	0.64	43.70

M5K-06	3/8	6GS-	GS-06GS1F-2	-----	32-32	1.00	20.70
M5K-08	1/2	8GS-	GS-08GS1F-2	-----	32-22mm	1.84	23.90

J2AT-06	3/8	6GS-	GS-06GS1F-2	-----	32-32	1.50	21.35
---------	-----	------	-------------	-------	-------	------	-------

Note: Die Set and Digital Setting information are to suit the Gates GC32-XD crimper only.
 Hose with XTF & MTF variations use the same crimp dimensions as the standard hose.

GL Fittings (Bubble Crimp)



Hose Part Number	Size (in.)	Fitting Type	Ferrule Description	Tail Length +/- 2.5(mm)	Die Set	Digital Setting	Crimp OD +/- 0.25(mm)
MT500-40	2 1/2	40GL-	1-pc GL	10.65	32-86	0.55	71.10
MT500-48	3	48GL-	1-pc GL	10.65	96-87*	2.30*	86.60*

GMV-40	2 1/2	40GL-	1-pc GL	10.90	32-86	1.10	72.15
GMV-48	3	48GL-	1-pc GL	11.70	96-87*	-----	88.15*
GMV-56	3 1/2	56GL-	1-pc GL	16.00	96-88*	-----	101.60*
GMV-64	4	64GL-	1-pc GL	14.00	96-89*	-----	114.30*

MULTIMASTER-40	2 1/2	40GL-	1-pc GL	10.90	32-86	1.30	72.40
MULTIMASTER-48	3	48GL-	1-pc GL	11.70	96-87*	-----	87.40*
MULTIMASTER-64	4	64GL-	1-pc GL	14.00	96-89*	-----	114.35*

*Note: Data and dies for use with GC96 Crimper.

www.hardyspicer.com.au

Document No:	HSCRIMPCAT
Issue:	15.1
Issue Date:	28/01/21

This catalogue is the copyright of Hardy Spicer

Note: Die Set and Digital Setting information are to suit the Gates GC32-XD crimper only. Hose with XTF & MTF variations use the same crimp dimensions as the standard hose.

Notes

Crimp Dimensions

www.hardyspicer.com.au

Document No:	HSCRIMPCAT
Issue:	15.1
Issue Date:	28/01/21

This catalogue is the copyright
of Hardy Spicer

Crimp Dimensions

Notes

Notes section with horizontal lines for writing. The area contains two large, diagonal, semi-transparent watermarks of the Hardy Spicer logo and tagline.

www.hardyspicer.com.au

Document No:	HSCRIMPCAT
Issue:	15.1
Issue Date:	28/01/21

This catalogue is the copyright of Hardy Spicer

Locations

QUEENSLAND

Darra

T (07) 3117 2800

E salesdarra@hardyspicer.com.au

Eagle Farm

T (07) 3166 2500

E salesbb@hardyspicer.com.au

Mackay

T (07) 4914 2100

E saleshmk@hardyspicer.com.au

Townsville

T (07) 4795 3400

E saleshtv@hardyspicer.com.au

SOUTH AUSTRALIA

Adelaide

T (08) 8349 6400

E saleshal@hardyspicer.com.au

TASMANIA

Hobart

T (03) 6272 6907

E hobartorders@hardyspicer.com.au

WESTERN AUSTRALIA

Bunbury

T (08) 9725 7033

E salesbunbury@hardyspicer.com.au

Kalgoorlie

T (08) 9091 1443

E saleshkg@hardyspicer.com.au

Welshpool

T (08) 9258 6300

E perthsales@hardyspicer.com.au

VICTORIA

Dandenong

T (03) 9799 3250

E saleshdn@hardyspicer.com.au

Sunshine

T (03) 9357 0233

E saleshcf@hardyspicer.com.au

NEW SOUTH WALES

Newcastle

T (02) 4964 4955

E saleshnc@hardyspicer.com.au

Sydney

T (02) 9600 6333

E saleshsn@hardyspicer.com.au

Illawarra

T (02) 4229 2381

E workshop@danielengineering.com.au

VISIT US ONLINE

▶ hardyspicer.com.au