

## SABRE DIFFUSION ABRASION HOSE SLEEVE

### ABRASION TESTED TO 200,000 CYCLES

#### Features:

- Size Diameters from 18mm up to 180mm
- Diffusion Abrasion Sleeve ultra tight construction contains and diffuses high pressure ruptures/bursts from pin hole leaks
- Unique industry leading anti-static properties
- Highly abrasion resistant
- UV stable
- Made from nylon
- Line of sight operator specification EN982 and and ISO 3457-2003



#### Specifications:

- FRAS Rated
- Flame resistant | ISO 6805:1994 Clause 15
- MDG | 3608 Compliant
- MSHA Approved
- Electrical Resistance | ISO 6805:1994 Clause 14
- Abrasion | ISO 6945
- Burst | 800 BAR
- Pin Hole Testing | 1mm pin hole test (prevention of fluid injection)
- Temperature Range | \* -50 to + 140 C"
- Melting Point | 220° C

PART #	ROUND I.D (mm)	FLAT I.D (mm)
HS-17	17	30
HS-20	20	34
HS-23	23	39
HS-25	25	42
HS-27	27	45
HS-31	31	52
HS-36	36	57
HS-40	40	66
HS-44	44	72
HS-47	47	77
HS-55	55	89
HS-60	60	97
HS-73	73	118
HS-75	75	121
HS-93	93	149
HS-112	112	179